# $3M^{TM}$ MetPak M HSHM Press-Fit Socket

### 2 mm Type E, 200 Signal Contacts, 8 Rows, Right Angle

<ul> <li>Modular/scalable format IEC 61076-4-10</li> <li>101 mated lines per linear inch</li> <li>Dual beam contact construction for high n</li> <li>End-to-end stackable with 8 row 3M<sup>™</sup> Me HM and HSHM products</li> <li>Mates with 3M<sup>™</sup> MetPak<sup>™</sup> HSHM headen</li> <li>See the Regulatory Information Appendix the "RoHS compliance" section of www.3mconnector.com for compliance in</li> </ul>	reliability etPak™ rs x (RIA) in
Date Modified: October 11, 2010	TS-2022-B Sheet 1 of 3

## **Physical**

#### Insulation:

Material:	High Temperature Thermoplastic (LCP)
Flammability:	UL 94V-0
<b>Contact:</b>	
Material:	Copper Alloy
Plating:	See Ordering Information
Marking:	3M Logo, Part Number, Revision, Date Code

### Performance

### Mechanical:

Normal Force (Nominal):	0.57 N [58 g] Signal
Engagement Force (Nominal):	0.32 N [33 g] Signal
Separation Force (Nominal):	0.20 N [20 g] Signal
Wipe (Nominal, Shortest Contact):	2.67 mm [0.105 in] Signal
Mate/Unmate Cycles:	250
Application:	This module is not suitable for stand-alone use.
Electrical:	
Current Rating (Fully Loaded):	1 A @ 70°C Signal
Insulation Resistance:	$1 \text{ x } 10^4 \text{ M}\Omega @ 100 \text{ V}_{\text{DC}}$
Withstanding Voltage:	$750\mathrm{V_{RMS}}$

### **Environmental**

**Temperature Rating:** -55° C to 125° C


UL File No.: E68080

MetPak is a trademark of 3M Company.

# $3M^{TM}$ MetPak TM HSHM Press-Fit Socket

### 2 mm Type E, 200 Signal Contacts, 8 Rows, Right Angle

HM Series




**3M** Electronic Solutions Division Interconnect Solutions http://www.3Mconnector.com

## $3M^{TM}$ MetPak M HSHM Press-Fit Socket

## 2 mm Type E, 200 Signal Contacts, 8 Rows, Right Angle

HM Series



#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



**3M Electronics Solutions Division** 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3Mconnector.com

Please recycle. Printed in USA. © 3M 2010. All rights reserved. RIA-2217B-E