



Characteristics:

- ESD Brushes are ideal for removing dust, dirt and left over materials from printed circuit boards (PCB) and other static sensitive components
- Brushes minimize static charge generation and remove electrostatic charges to ground when held by grounded personnel
- RTT Resistance: 1 x 10³ to <1 x 10⁵ ohms tested per modified ANSI/ESD S4.1
- Bristle Material: Conductive synthetic yarn

Item	Handle	Bristle	Overall	Overall	Bristle	Bristle	Bristle
	Material	Hardness	Length	Width	Length	Width	Height
<u>36090</u>	Aluminum	Soft	4-11/16" (120 mm)	1/8" (3 mm)	1/2" (13 mm)	5/16" (8 mm)	5/16" (8 mm)

Designed to fulfill ANSI/ESD S20.20 requirement to ground all conductors at ESD workstation.

ESD Handbook TR20.20 Table 1 lists under Typical Static Electricity Sources "Brushes (camel/pig hair and synthetic bristles)."

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." (TR 20.20 section 2.4)

Unless otherwise noted, tolerance is ±10%.

Specifications and procedures subject to change without notice.

Made in Israel

ESD BRUSH, CONDUCTIVE, ROUND ALUMINUM HANDLE, BLACK SOFT BRISTLES, 1/8 IN

MENDA

3651 WALNUT AVE., CHINO, CA 91710

PHONE: (909) 627-2453 WEBSITE: MendaPump.com DRAWING NUMBER 36090 DATE: July 2018